

# Purolator®

## PAF 11™


Medium Efficiency, Synthetic Pleated Filters

### Introduction

- Purolator's PAF 11 filters are medium efficiency, self-supported, extended surface, pleated air filters.
- Specifically manufactured for system applications requiring high efficiency, non-shedding filtration media.
- Outperforms similar products with respect to initial efficiency, and average efficiency providing optimum filter service life.
- Effective in single filter applications or as improved pre-filter substitutes for disposables, permanent metal filters or media pad/frame filters.
- Industry applications: Prefiltration for hospitals, health care facilities, food processing plants, telecommunications, pharmaceutical and semi-conductor manufacturing, etc.
- MERV 11 (Minimum Efficiency Reporting Value) based on ASHRAE Test Standard 52.2-2007

### Media and Support

- Synthetic media made up of continuous hydrophobic fibers which do not absorb moisture, and can withstand turbulent, high velocity conditions.
- Fibers are thermally bonded to eliminate the need for chemical binders that could promote microbial growth or generate VOCs.
- Improved overall particle size efficiency due to continuous fiber structure and dual stage electrostatic enhancement which captures an increased amount of smaller particulate than conventional glass media.
- Media support: Continuously bonded to a corrosion resistant, expanded metal grid allowing a 96% open face area.
- Pleat configuration: Formed into aerodynamic, semi-tapered, wedge-shaped pleats expanding its capability to capture contaminants.



### Construction features

- Frame: Enclosed in a two-piece, high wet-strength beverage board frame.
- Assembly: A fully bonded double wall frame combines with the integral corner flaps and forms a rugged, durable filter which will not rack, warp or leak under normal operating conditions.
- To assure no dirty air bypass, the media pack is securely bonded to the periphery of the enclosure frame with solvent-free water based glue.
- U.L. Classification: Class 2 approved and listed. Tested in accordance with U.L. Standard 900.
- In 4" models, accurate pleat alignment is maintained by die-cut pleat spacers on the upstream side.
- Maximum operating temperature: ≤200°F.

# PAF 11™

Medium Efficiency, Synthetic Pleated Filters

## Suggested Product Specifications

1. The filter shall be the PAF 11 as manufactured by Purolator
2. Air filters shall be (2") and (4") deep, medium efficiency, pleated media, disposable panel type.
3. The filter media shall be synthetic media as brand named to Purolator.
4. The filter media shall be bonded to a corrosion resistant, expanded metal support grid with a 96% open face area.
5. To assure no dirty air bypass, the media grid assembly shall be bonded to all interior surfaces of the frame with solvent-free water based glue.
6. The support grid shall be formed into a wedge configuration to optimize use of the filter media.
7. To maintain accurate pleat alignment, die-cut diagonal frame members shall be bonded to the media pack upstream and downstream.

## Performance Data: PAF 11

Series	PAF 11 Model Number	Nominal (1) Size WxHxD	Actual Size WxHxD	CFM(2) Capacity	Resist *W.G.	Resist *W.G. Final(3)	Sq. Ft.	Media area/Sq. Ft. Face Area
<b>2</b> 15 pleats per lineal foot of face area	PAF11-STD2	10x20x2	9½ x 19½ x 1¾	700	.31	1.00	6.1	4.6
	PAF11-STD2	12X12X2	11½ x 11½ x 1¾	900	.31	1.00	3.1	4.6
	PAF11-STD2	12X20X2	11½ x 19½ x 1¾	850	.31	1.00	7.1	4.6
	PAF11-STD2	12X24X2	11¾ x 23¾ x 1¾	1000	.31	1.00	8.5	4.6
	PAF11-STD2	14X20X2	13½ x 19½ x 1¾	975	.31	1.00	8.6	4.6
	PAF11-STD2	14X25X2	13½ x 24½ x 1¾	1215	.31	1.00	10.8	4.6
	PAF11-STD2	15X20X2	14½ x 19½ x 1¾	1040	.31	1.00	9.1	4.6
	PAF11-STD2	16X16X2	15½ x 15½ x 1¾	890	.31	1.00	5.7	4.6
	PAF11-STD2	16X20X2	15½ x 19½ x 1¾	1100	.31	1.00	9.6	4.6
	PAF11-STD2	16X24X2	15½ x 23¾ x 1¾	1335	.31	1.00	11.6	4.6
	PAF11-STD2	16X25X2	15½ x 24½ x 1¾	1400	.31	1.00	12.1	4.6
	PAF11-STD2	18X20X2	17¾ x 19½ x 1¾	1250	.31	1.00	11.2	4.6
	PAF11-STD2	18X22X2	17¾ x 21½ x 1¾	1500	.31	1.00	12.3	4.6
	PAF11-STD2	18X24X2	17¾ x 23¾ x 1¾	1500	.31	1.00	13.4	4.6
	PAF11-STD2	18X25X2	17¾ x 24½ x 1¾	1550	.31	1.00	14.0	4.6
	PAF11-STD2	20X20X2	19½ x 19½ x 1¾	1400	.31	1.00	12.2	4.6
	PAF11-STD2	20X24X2	19¾ x 23¾ x 1¾	1665	.31	1.00	14.6	4.6
	PAF11-STD2	20X25X2	19½ x 24½ x 1¾	1750	.31	1.00	15.3	4.6
	PAF11-STD2	20X30X2	19-½ x 29½ x 1¾	2000	.31	1.00	13.1	4.6
	PAF11-STD2	24X24X2	23¾ x 23¾ x 1¾	2000	.31	1.00	17.6	4.6
PAF11-STD2	25X25X2	24½ x 24½ x 1¾	2000	.31	1.00	19.1	4.6	
<b>4</b> 11 pleats per lineal foot of face area	PAF11-STD4	12X24X4	11¾ x 23¾ x 3¾	1250	.22	1.00	14.0	7.0
	PAF11-STD4	16X20X4	15¾ x 19¾ x 3¾	1400	.22	1.00	14.9	7.0
	PAF11-STD4	16X25X4	15¾ x 24¾ x 3¾	1750	.22	1.00	18.6	7.0
	PAF11-STD4	18X24X4	17¾ x 23¾ x 3¾	1875	.22	1.00	20.4	7.0
	PAF11-STD4	20X20X4	19¾ x 19¾ x 3¾	1750	.22	1.00	19.1	7.0
	PAF11-STD4	20X24X4	19¾ x 23¾ x 3¾	2050	.22	1.00	23.0	7.0
	PAF11-STD4	20X25X4	19¾ x 24¾ x 3¾	2170	.22	1.00	24.0	7.0
	PAF11-STD4	24X24X4	23¾ x 23¾ x 3¾	2500	.22	1.00	28.0	7.0
	PAF11-STD4	25X29X4	24½ x 28-½ x 3¾	3150	.22	1.00	34.6	7.0

- (1) Width and height dimensions are interchangeable. The PAF 11 may be installed with pleats running vertical or horizontal.
- (2) Capacity ratings are recommended levels. Resistance to airflow data is based on ASHRAE 52.2-2007 Test Methods. Data based on 24x24 size at a test velocity of 492 FPM.
- (3) The recommended final operating resistance is typical of systems currently in operation. The PAF 11 can be operated to higher or lower final resistance levels without materially affecting filter efficiency.
- (4) The PAF 11 pleated filter is UL Class 2 approved and listed. Testing on this product was performed in accordance with UL Standard 900. Suggested operating temperatures: not to exceed 200°F (93°C).

P-PAF11-209



www.purolatorair.com



CLARCOR Air Filtration Products  
100 River Ridge Circle • Jeffersonville, IN 47130  
Customer Care Team: 1-866-925-2247 • Fax: 1-800-784-3458  
Email: info@purolatorair.com • www.purolatorair.com

Distributed by:

© 2009 CLARCOR Air Filtration Products.  
CLARCOR Air Filtration Products has a policy of continuous product research and development and reserves the right to change design and specifications without notice.  
Terms and Conditions of Sale can be accessed in the "LOGIN" section at www.purolatorair.com